Change every 50 hours

CASE SKID STEER LOADERS SV185 (2012-2014)



ENGINE Shibaura ISM N844LT Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30
Check every 10 hours, change every 250 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30

CHAIN DRIVE UNIT Capacity: 7,4 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30
Check every 500 hours, change eve	ry 1000 hours	

HYDRAULIC SYSTEM Capacity: 15 liter (Hydraulic tank), Capacity: 32,2 liter (System)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30
Check every 10 hours, change every 1000 hours		

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
Change every 10 hours	

CASE SKID STEER LOADERS SV185 (2012-2014)



COOLING SYSTEM Capacity: 15,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Chack avery 10 hours, change over	1,1000 hours	·

Check every 10 hours, change every 1000 hours

TRAVEL REDUCTION UNIT Capacity: 1 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Change every 500 hours		
lio-		OL BALTE

Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Initial service		Moderate
USE		CLIMATE

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.