

# CASE WHEELED EXCAVATORS WX WX185 SERIES 2 (2008-2018)



**ENGINE** Case 667TA/MEB  
Capacity: 16 liter

**USE**  
Normal

**CLIMATE**  
Moderate

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40**

**DIFFERENTIAL FRONT**  
Capacity: 11,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**DIFFERENTIAL REAR**  
Capacity: 12 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**TRANSMISSION**  
Capacity: 2,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**TRAVEL REDUCTION UNIT FRONT**  
Capacity: 1,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**TRAVEL REDUCTION UNIT REAR**  
Capacity: 1 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**HYDRAULIC SYSTEM**  
Capacity: 140 liter (Hydraulic tank), Capacity: 260 liter (System)

**USE**  
Normal

**CLIMATE**  
Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 68**

## GREASE POINTS/NIPPLES

**USE**  
Normal

**CLIMATE**  
Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

# CASE WHEELED EXCAVATORS WX WX185 SERIES 2 (2008-2018)

**COOLING SYSTEM**

Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

**SWING REDUCTION UNIT**

Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*