

| ENGINE 3306 Capacity: 27,5 liter | | |
|-------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Kroontrak MTH 10W-30 | Asyntho 5W-30 |

Check every 10 hours, change every 1 months/ 250 hours

| FINAL DRIVES Capacity: 13,5 liter | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 Gear Oil Alcat 50 | | |
| Check every 1 months/ 250 hours, change every 12 months/ 2000 hours | | |
| USE | | CLIMATE |

| USE | | CLIMATE |
|---|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Check every 1 months/ 250 hours, change every 12 months/ 2000 hours | | |

| TRANSMISSION Capacity: 148 liter | | |
|-------------------------------------|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Check every 10 hours, change every 6 months/ 1000 hours

| use Normal | climate Cold |
|--------------------------|-----------------|
| PRODUCT RECOMMENDATION 1 | |
| Gear Oil Alcat 10W | |
| | 1 |

Check every 10 hours, change every 6 months/ 1000 hours



| HYDRAULIC SYSTEM Capacity: 47,3 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Gear Oil Alcat 30 | |
| Check every 10 hours, change every 2000 | hours/ 12 months | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |
| Check every 10 hours, change every 2000 | hours/ 12 months | |
| USE | | CLIMATE |
| Biodegradable oil | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |
| Check every 10 hours, change every 2000 | hours/ 12 months | |
| | | |
| GREASE POINTS/NIPPLES | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

| CLIMATE |
|------------|
| Moderate |
| ENDATION 2 |
| e |
| |



| COOLING SYSTEM Capacity: 74 liter | | | |
|---|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Preferred, extended | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| Coolant SP 17 | | | |
| Check every 10 hours, change every 48 m | onths/ 6000 hours | | |
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF | |

Check every 10 hours, change every 24 months/ 3000 hours

| PIVOT SHAFTS Capacity: 5 liter | | |
|-----------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Check every 50 hours | | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Check every 50 hours

| RECOIL SPRING COMPARTMENT Capacity: 25 liter | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Check every 3 months/ 500 hours | | |

| USE | CLIMATE |
|---------------------------------|---------|
| Normal | Arctic |
| PRODUCT RECOMMENDATION 1 | |
| Gear Oil Alcat 10W | |
| Check every 3 months/ 500 hours | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the



information contained herein is subject to changes without notification.