

ENGINE C9 Acert		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every 3 mo	nths/ 500 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	
Check every 10 hours, change every 3 mo	nths/ 500 hours	
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		
Check every 10 hours, change every 3 mo	nths/ 500 hours	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Check every 10 hours, change every 3 mo	nths/ 500 hours	
TRANSMISSION Powershift Capacity: 148 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 10 hours, change every 6 mo	nths/ 1000 hours	
USE		CLIMATE
Normal		Cold

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

Check every 10 hours, change every 6 months/ 1000 hours



HYDRAULIC SYSTEM Capacity: 55,5 liter (Hydraulic tank)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Multifleet SCD 30	Gear Oil Alcat 30		
Check every 10 hours, change every 2000 hours/ 12 months			
USE		CLIMATE	
Normal		Moderate	

Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Asyntho 5W-30
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate

Check every 10 hours, change every 2000 hours/ 12 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 70 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	
Check every 10 hours, change every 72 m	12000 hours



PIVOT SHAFT Capacity: 5 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
Check every 1 months/ 250 hours	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Check every 1 months/ 250 hours	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Check every 1 months/ 250 hours	
RECOIL SPRING COMPARTMENT Capacity: 25 liter (each)	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	

Gear Oil Alcat 50

Check every 3 months/ 500 hours

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Check every 3 months/ 500 hours

USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Check every 3 months/ 500 hours	<u>b</u>



TRAVEL REDUCTION UNIT Capacity: 13,5 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 50	

Check every 500 hours, change every 12 months/ 2000 hours

USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Check every 500 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Severe		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Charle avery 500 hours shares avery 12	mantha/2000 haura	

Check every 500 hours, change every 12 months/ 2000 hours

WINCH Capacity: 67,2 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
0 1 1 1 10501 1	0 // / / 000 /	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.