

ENGINE 3406E ATAAC Capacity: 37 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Asyntho 5W-30

Check every 10 hours, change every 1 months/ 250 hours

TRANSMISSION Capacity: 155 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 10 hours, change every 6 mo	nths/ 1000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		

Gear Oil Alcat 10W

Check every 10 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 3 months/ 500 hours

USE	CLIMATE
Fluid analysis	Cold
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

Check every 3 months/ 500 hours

HYDRAULIC SYSTEM Capacity: 72 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Charle grant 10 hours, change grant 2000 hours/12 months		

Check every 10 hours, change every 2000 hours/ 12 months



USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 10 hours, change every 2000) hours/ 12 months	
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every 2000) hours/ 12 months	
USE		CLIMATE
Fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Check every 3 months/ 500 hours		
USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 3 months/ 500 hours		
USE		CLIMATE
Biodegradable oil, fluid analysis		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 3 months/ 500 hours		
GREASE POINTS/NIPPLES		
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1		

MoS2 Grease EP 2



COOLING SYSTEM Capacity: 83,5 liter	
use Normal	сымате Moderate
PRODUCT RECOMMENDATION 1 Coolant SP 17	

Check every 10 hours, change every 48 months/ 6000 hours

HUB VARIABLE FAN Capacity: 3,1 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 6 months/ 1000 hours, change every 24 months/ 3000 hours		

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Check every 6 months/ 1000 hours, change every 24 months/ 3000 hours

PIVOT SHAFT Capacity: 40 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	

Check every 10 hours

use Normal	climate Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Check every 10 hours

USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Check every 10 hours	·



RECOIL SPRING COMPARTMENT Capacity: 65 liter (each)	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

TRACK IDLERS			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 40			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 30			

TRACK ROLLERS				
USE	CLIMATE			
Normal	Mediterranean			
PRODUCT RECOMMENDATION 1				
Multifleet SCD 40				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Multifleet SCD 30				



TRAVEL REDUCTION UNIT Capacity: 12,5 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Chack avery 1 months/250 hours change	avery 12 months/2000 hours	

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

WINCH Capacity: 15 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 500 hours		
USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 500 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.