

CATERPILLAR FELLER BUNCHERS 1490



ENGINE Cummins QSC
Capacity: 23,8 liter

| USE | | CLIMATE |
|-------------------------------|-------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | |

HYDRAULIC HOOD TILT SYSTEM
Capacity: 6,5 liter (Hydraulic tank)

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 10 hours

| USE | | CLIMATE |
|-------------------------------|--------------------------|-----------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 10 hours

HYDRAULIC SYSTEM
Capacity: 323 liter (Hydraulic tank)

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 10 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|-------------------------------|--------------------------|-----------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 10 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM VARIABLE PITCH FLEXXAIRE FAN
Capacity: 0,65-1,22 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

CATERPILLAR FELLER BUNCHERS 1490



COOLING SYSTEM

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

SWING REDUCTION UNIT

Capacity: 10 liter

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|-------------------------------|--------------------------|-----------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Change every 250 hours

| USE | | CLIMATE |
|-------------------------------|--------------------------|-----------------------------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Change every 250 hours

CATERPILLAR FELLER BUNCHERS 1490**TRAVEL REDUCTION UNIT**

Capacity: 9 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.