PRODUCT RECOMMENDATION

CATERPILLAR FELLER BUNCHERS 541
(TILL 2012)

ENGINE C9 Acert
Capacity: 39 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**
Check every 10 hours, change every 1 months/ 250 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Agrisynth LSP 10W-40	**Multifleet SHPD 10W-40**	
Check every 10 hours, change every 1 months/ 250 hours		

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Agridiesel CRD+ 15W-40	**Multifleet SHPD 15W-40**	
Check every 10 hours, change every 1 months/ 250 hours		

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Synfleet SHPD 10W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 10W-40**
Check every 10 hours, change every 1 months/ 250 hours		

HYDRAULIC HOOD TILT SYSTEM
Capacity: 3,8 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**
Check every 10 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FELLER BUNCHERS 541
(TILL 2012)

HYDRAULIC SYSTEM
Capacity: 318 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 10 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 10 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM VARIABLE PITCH FLEXXAIRE FAN
Capacity: 0,65-1,22 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM
Capacity: 36 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 72 months/ 12000 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FELLER BUNCHERS 541
(TILL 2012)

SWING REDUCTION UNIT
Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	
Change every 250 hours		

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		

TRAVEL REDUCTION UNIT
Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367