CATERPILLAR FELLER BUNCHERS 551



	CLIMATE
	Mediterranean
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
onths/ 250 hours	
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Multifleet SHPD 10W-40	
onths/ 250 hours	· · · ·
	CLIMATE
	Mediterranean
PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	
onths/ 250 hours	
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40
onths/ 250 hours	
	CLIMATE
	Mediterranean
	CLIMATE
	Moderate
	Dieselfleet CD+ 15W-40 onths/ 250 hours PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40 onths/ 250 hours PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40 onths/ 250 hours PRODUCT RECOMMENDATION 2 Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

Check every 10 hours

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

CATERPILLAR FELLER BUNCHERS 551



Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Normal		Moderate		
USE		CLIMATE		
Check every 10 hours, change every 6 months/ 1000 hours				
Gear Oil Alcat 30				
PRODUCT RECOMMENDATION 1				
Normal		Mediterranean		
USE		CLIMATE		
HYDRAULIC SYSTEM Capacity: 318 liter (Hydraulic tank)				

Check every 10 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM VARIABLE PITCH FLEXXAIRE FAN Capacity: 0,65-1,22 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 36 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every 72 months/ 12000 hours		

CATERPILLAR FELLER BUNCHERS 551



SWING REDUCTION UNIT Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		
TRAVEL REDUCTION UNIT Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

use Normal		climate Arctic
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.