

# CATERPILLAR FOREST HARVESTERS

## 560B TRA00001 ->



**ENGINE** 3056E ATAAC  
Capacity: 30 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-----------------------------|--------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Asyntho 5W-30</b>     |

*Check every 10 hours, change every 1 months/ 250 hours*

**BOGIE FRONT**  
Capacity: 22 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Change every 250 hours*

**HUB REDUCTIONS FRONT**  
Capacity: 4 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

# CATERPILLAR FOREST HARVESTERS

## 560B TRA00001 ->



### HYDRAULIC SYSTEM

Capacity: 150 liter (Hydraulic tank)

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Gear Oil Alcat 30</b> |  |               |

Check every 10 hours, change every 6 months/ 1000 hours

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gear Oil Alcat 10W</b> |  |          |

Check every 10 hours, change every 6 months/ 1000 hours

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Biodegradable oil         |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Perlus Biosynth 46</b> |  |          |

Check every 10 hours, change every 6 months/ 1000 hours

### COOLING SYSTEM

Capacity: 50 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 17</b>     |  |          |

Check every 10 hours, change every 72 months/ 12000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.