PRODUCT RECOMMENDATION

# CATERPILLAR MOTOR GRADERS 12H 2GS
(1995-1996)

**ENGINE** 3306 Turbo
Capacity: 29 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agridiesel CRD+ 15W-40** | **Synfleet SHPD 10W-40** | **Dieselfleet CD+ 15W-40** |
| *Check every 10 hours, change every 1 months/ 250 hours* | | |
| USE | | CLIMATE |
| Normal, fuel with sulfur content > 1,5% by weight | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agridiesel CRD+ 15W-40** | **Synfleet SHPD 10W-40** | **Dieselfleet CD+ 15W-40** |
| *Check every 10 hours, change every 1 months/ 125 hours* | | |

**TANDEM DRIVE**
Capacity: 64 liter (each side)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gear Oil Alcat 30** | **Gear Oil Alcat 50** | |
| *Check every 1 months/ 250 hours, change every 12 months/ 2000 hours* | | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| **Gear Oil Alcat 10W** | | |
| *Check every 1 months/ 250 hours, change every 12 months/ 2000 hours* | | |

**TRANSAXLE**
Capacity: 47 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gear Oil Alcat 30** | **Gear Oil Alcat 50** | |
| *Check every 1 months/ 250 hours, change every 6 months/ 1000 hours* | | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| **Gear Oil Alcat 10W** | | |
| *Check every 1 months/ 250 hours, change every 6 months/ 1000 hours* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR MOTOR GRADERS 12H 2GS
(1995-1996)

## HYDRAULIC SYSTEM
Capacity: 38 liter (Hydraulic tank)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Multifleet SCD 30** | **Gear Oil Alcat 30** | |

*Check every 10 hours, change every 2000 hours/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agridiesel CRD+ 15W-40** | **Kroontrak MTH 10W-30** | **Asyntho 5W-30** |

*Check every 10 hours, change every 2000 hours/ 12 months*

## WHEEL SPINDLE BEARING FRONT
Capacity: 0,5 liter (each wheel)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gear Oil Alcat 30** | **Gear Oil Alcat 50** | |

*Check every 3 months/ 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| **Gear Oil Alcat 10W** | | |

*Check every 3 months/ 500 hours*

## COOLING SYSTEM
Capacity: 45 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Coolant SP 15+** | **Coolant SP 12** | **Coolant -38 Organic NF** |

*Check every 10 hours, change every 24 months/ 3000 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CATERPILLAR MOTOR GRADERS 12H 2GS
(1995-1996)

**CIRCLE DRIVE GEARBOX**
Capacity: 7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gearlube GL-5 85W-140** | **Unigear LS GL-3/GL-5 85W-140** | |
| *Check every 10 hours, change every 2000 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **SP Gear 1011** | **Syngear TDL 75W-90** | **Gearlube GL-5 80W-90** |
| *Check every 10 hours, change every 2000 hours/ 12 months* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367