## CATERPILLAR MULTI TERRAIN LOADERS 287C CATERPILLAR C3.4 DIT (2007-2011)



ENGINE 3044C DIT Capacity: 10 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Check every 10 hours, change every 500 hours/ 12 months				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40			

Check every 10 hours, change every 500 hours/ 12 months

FINAL DRIVES Capacity: 1 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 250 hours, change every	soo hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90
Check every 250 hours, change every	500 hours	·
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Change every 250 hours	·	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90
Change every 250 hours	•	·

## CATERPILLAR MULTI TERRAIN LOADERS 287C CATERPILLAR C3.4 DIT (2007-2011)



**Agrifluid HT** 

HYDRAULIC SYSTEM Capacity: 42 liter, Capacity: 57 liter (System)					
USE		CLIMATE			
Normal		Mediterranean			
PRODUCT RECOMMENDATION 1					
Gear Oil Alcat 30					
Check every 10 hours, change every 2000 hours/ 12 months					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			

Agrifluid HT-Plus Kroontrak MTH 10W-30

Check every 10 hours, change every 2000 hours/ 12 months

COOLING SYSTEM Capacity: 13,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 17			
Check every 10 hours, change every 72 months/ 12000 hours			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.