

# CATERPILLAR MULTI TERRAIN LOADERS

## 297C CATERPILLAR C3.4 DIT (2007-2011)



**ENGINE C3.4 DIT**  
Capacity: 10 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrisynth LSP 10W-40</b>	<b>Multifleet SHPD 10W-40</b>	

*Check every 10 hours, change every 500 hours/ 12 months*

**FINAL DRIVES**  
Capacity: 1 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

*Check every 250 hours, change every 500 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Gearlube Racing 75W-140</b>	<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Check every 250 hours, change every 500 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

*Change every 250 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Gearlube Racing 75W-140</b>	<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Change every 250 hours*

# CATERPILLAR MULTI TERRAIN LOADERS

## 297C CATERPILLAR C3.4 DIT (2007-2011)



### HYDRAULIC SYSTEM

Capacity: 42 liter, Capacity: 57 liter (System)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

*Check every 10 hours, change every 2000 hours/ 12 months*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>	<b>Agrifluid HT</b>

*Check every 10 hours, change every 2000 hours/ 12 months*

### COOLING SYSTEM

Capacity: 13,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

*Check every 10 hours, change every 72 months/ 12000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.