CATERPILLAR RIGID DUMP TRUCKS 773D 7CS (1996-2001)



ENGINE 3412E Capacity: 76 liter		
USE		CLIMATE
Extended drain (max)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	

Check every 10 hours, change every 1 months/ 250 hours

USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth MSP 5W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Check every 10 hours, change every 1 months/ 250 hours

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40	

Check every 10 hours, change every 1 months/ 250 hours

Agrisynth LSP Ultra 10W-40	Agridiesel MSP 15W-40	Armado Synth LSP Ultra 10W-40
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE

Check every 10 hours, change every 1 months/ 250 hours

DIFFERENTIAL REAR

Capacity: 140 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION + TORQUE CONVERTER Capacity: 53 liter, Capacity: 72 liter (Complete)			
USE		CLIMATE	
Flexible (max)		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Check every 10 hours, change every 6 months/ 1000 hours			
USE		CLIMATE	
Flexible (max)		Cold	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Check every 10 hours, change every 6 months/ 1000 hours			

CATERPILLAR RIGID DUMP TRUCKS 773D 7CS (1996-2001)



YDRAULIC SYSTEM HOIST + BRAKE apacity: 133 liter (Hydraulic tank), Capacity: 277 liter (Total)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every 6 months/ 1000 hours		

CENTRAL LUBRICATION SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

FAN DRIVE BEARINGS

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
USE	CLIMATE
Light Duty	Moderate
PRODUCT RECOMMENDATION 1	
HT Q9 High Grade Grease	

WHEEL BEARINGS FRONT

Capacity: 4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 137 liter	
USE	CLIMATE
Extended	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	
Check every 10 hours, change every 24 months/ 3000 hou	ırs

CATERPILLAR RIGID DUMP TRUCKS 773D 7CS (1996-2001)



POWER STEERING HYDRAULIC SYST Capacity: 34 liter (Hydraulic tank), Capac		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 6 m	onths/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 10 hours, change every 6 m	onths/ 1000 hours	
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every 6 m	onths/ 1000 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.