

CATERPILLAR SOIL COMPACTORS 825K

233/SEE (2014 AND AFTER)



ENGINE C15 Acert
Capacity: 34 liter

USE	CLIMATE
Preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agridiesel MSP 15W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Fluid analysis, preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40

Check every 1 months/ 250 hours

USE	CLIMATE
Fluid analysis, preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agridiesel MSP 15W-40	Armado Synth LSP Ultra 10W-40

Check every 1 months/ 250 hours

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth MSP 5W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Fluid analysis, alternative	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 1 months/ 250 hours

CATERPILLAR SOIL COMPACTORS 825K

233/SEE (2014 AND AFTER)



USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth MSP 5W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30
<i>Check every 1 months/ 250 hours</i>		

DIFFERENTIAL FRONT + HUB REDUCTIONS

Capacity: 1,5 liter (special additive), Capacity: 100 liter (Total)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR + HUB REDUCTIONS

Capacity: 110 liter

USE		CLIMATE
Fluid analysis, preferred		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
<i>Check every 3 months/ 500 hours</i>		

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
<i>Check every 3 months/ 500 hours</i>		

USE		CLIMATE
Fluid analysis, preferred		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
<i>Check every 3 months/ 500 hours</i>		

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
<i>Check every 1 months/ 250 hours, change every 12 months/ 2000 hours</i>		

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
<i>Check every 1 months/ 250 hours, change every 12 months/ 2000 hours</i>		

CATERPILLAR SOIL COMPACTORS 825K

233/SEE (2014 AND AFTER)



USE		CLIMATE
Alternative (acceptable)		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
<i>Check every 1 months/ 250 hours, change every 12 months/ 2000 hours</i>		

TRANSMISSION Powershift Capacity: 66 liter		
USE		CLIMATE
Fluid analysis, preferred		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
<i>Check every 3 months/ 500 hours</i>		

USE		CLIMATE
Fluid analysis, preferred		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
<i>Check every 3 months/ 500 hours</i>		

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
<i>Check every 10 hours, change every 2000 hours/ 12 months</i>		

USE		CLIMATE
Alternative (acceptable)		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
<i>Check every 10 hours, change every 2000 hours/ 12 months</i>		

HYDRAULIC SYSTEM		
Capacity: 1 liter (Change capacity, special additive), Capacity: 134 liter (Hydraulic tank), Capacity: 2 liter (special additive), Capacity: 214 liter (Total)		

We are unable to give a standard recommendation for this component. Please contact our service department.

EXTERNAL GREASE POINTS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

CATERPILLAR SOIL COMPACTORS 825K

233/SEE (2014 AND AFTER)



GREASE POINTS/NIPPLES DRIVE SHAFT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		
<i>Change every 1000 hours/ 6 months</i>		

COOLING SYSTEM

Capacity: 116 liter

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
<i>Check every 12 months/ 2000 hours, change every 72 months/ 12000 hours</i>		

USE		CLIMATE
Fluid analysis, initial (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
<i>Check every 250 hours</i>		

USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
<i>Check every 3 months/ 500 hours</i>		

SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)

Capacity: 32 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.