

ENGINE C15 Acert		
Capacity: 34 liter		
USE		CLIMATE
Fluid analysis, preferred		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40
Check every 1 months/ 250 hours	·	
USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30
Check every 1 months/ 250 hours		
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40
Check every 10 hours, change every 3 mo	onths/ 500 hours	·
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30
Check every 10 hours, change every 3 mo	onths/ 500 hours	·
USE		CLIMATE
Initial service (alternative)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel CRD+ 15W-40	Dieselfleet MSP 15W-40
Change every 250 hours		·
USE		CLIMATE
Initial service (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30
Change every 250 hours		· ·

Change every 250 hours

DIFFERENTIAL FRONT + HUB REDUCTIONS

Capacity: 1,5 liter (special additive), Capacity: 90 liter (Total)

We are unable to give a standard recommendation for this component. Please contact our service department.



DIFFERENTIAL REAR + HUB REDUCTIONS

Capacity: 1,5 liter (special additive), Capacity: 90 liter (Total)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION Powershift Capacity: 62 liter		
USE		CLIMATE
Fluid analysis, preferred		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 3 months/ 500 hours	,	
USE		CLIMATE
Fluid analysis, preferred		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 3 months/ 500 hours		
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30	PRODUCT RECOMMENDATION 2 Gear Oil Alcat 50	
	Gear Oil Alcat 50	
Gear Oil Alcat 30 Check every 10 hours, change every 6 mo	Gear Oil Alcat 50	CLIMATE
Gear Oil Alcat 30 Check every 10 hours, change every 6 mo	Gear Oil Alcat 50	climate Cold
Gear Oil Alcat 30 Check every 10 hours, change every 6 mo use Alternative (acceptable) PRODUCT RECOMMENDATION 1	Gear Oil Alcat 50	
Gear Oil Alcat 30 Check every 10 hours, change every 6 mo use Alternative (acceptable)	Gear Oil Alcat 50	
Gear Oil Alcat 30 Check every 10 hours, change every 6 mo use Alternative (acceptable) PRODUCT RECOMMENDATION 1	Gear Oil Alcat 50	
Gear Oil Alcat 30 Check every 10 hours, change every 6 mo use Alternative (acceptable) PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W	Gear Oil Alcat 50	
Gear Oil Alcat 30 Check every 10 hours, change every 6 mo use Alternative (acceptable) PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W	Gear Oil Alcat 50	
Gear Oil Alcat 30 Check every 10 hours, change every 6 mo USE Alternative (acceptable) PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Check every 10 hours, change every 6 mo HYDRAULIC SYSTEM	Gear Oil Alcat 50	

PRODUCT RECOMMENDATION 1 Perlus Biosynth 46

Check every 10 hours, change every 18 months/ 3000 hours

USE	CLIMATE
Fluid analysis, preferred	Moderate
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	
Check every 1 months/ 250 hours	·



USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 200	0 hours/ 12 months	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40
Check every 10 hours, change every 200	0 hours/ 12 months	
USE		CLIMATE
Fluid analysis, alternative		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours		
USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40
Check every 1 months/ 250 hours		· · ·
CENTRAL LUBRICATION SYSTEM		
USE		CLIMATE

SE	CLIMATE
ormal	Moderate
RODUCT RECOMMENDATION 1	
loS2 Grease EP 2	
oS2 Grease EP 2	

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	



GREASE POINTS/NIPPLES DRIVE SHAFT SUPPORT BEARING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		
01 1 0 11 140001		

Check every 6 months/ 1000 hours

GREASE POINTS/NIPPLES DRIVE SHAFT UNIVERSAL JOINTS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

GREASE POINTS/NIPPLES STEERING COLUMN		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

COOLING SYSTEM Capacity: 83 liter		
USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 12 months, change every 72 months/ 12000 hours		
USE		CLIMATE
Fluid analysis, initial (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 500 hours		
USE		CLIMATE

PRODUCT RECOMMENDATION 2

Coolant SP 12

Check every 3 months/ 500 hours

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.