

# CATERPILLAR TELESCOPIC HANDLERS

## RT/TH TH340B (2004 AND AFTER)



**ENGINE** 3054E ATAAC  
Capacity: 8,4 liter

USE		CLIMATE
Normal (preferred)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Check every 10 hours, change every 500 hours/ 6 months*

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 500 hours/ 6 months*

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>

*Check every 10 hours, change every 500 hours/ 6 months*

### DIFFERENTIAL FRONT

Capacity: 10,5 liter, Capacity: 0,47 liter (Friction modifier)

We are unable to give a standard recommendation for this component. Please contact our service department.

### DIFFERENTIAL REAR

Capacity: 11 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

# CATERPILLAR TELESCOPIC HANDLERS

## RT/TH TH340B (2004 AND AFTER)



### HUB REDUCTIONS FRONT

Capacity: 0,7 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

### HUB REDUCTIONS REAR

Capacity: 0,7 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

### HYDRAULIC SYSTEM

Capacity: 66 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 10 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 10 hours, change every 1000 hours/ 12 months*

# CATERPILLAR TELESCOPIC HANDLERS

## RT/TH TH340B (2004 AND AFTER)



### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	

### COOLING SYSTEM

Capacity: 22,5-24,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

Check every 10 hours, change every 72 months/ 12000 hours

### SERVICE BRAKE SYSTEM

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.