

CATERPILLAR TRACKED EXCAVATORS

245B 1SJ (TILL 1992)

**ENGINE**

Capacity: 46,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

PRODUCT RECOMMENDATION 2

Multifleet SCD 30*Change every 250 hours/ 1 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40*Change every 250 hours/ 1 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 250 hours/ 1 months***FINAL DRIVES**

Capacity: 60,5 liter (each side)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Check every 1 months/ 250 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Check every 1 months/ 250 hours*

CATERPILLAR TRACKED EXCAVATORS

245B 1SJ (TILL 1992)



HYDRAULIC SYSTEM

Capacity: 403 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

COOLING SYSTEM

Capacity: 77,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

PUMP DRIVE

Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Check every 50 hours, change every 12 months/ 2000 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Check every 50 hours, change every 12 months/ 2000 hours*

CATERPILLAR TRACKED EXCAVATORS

245B 1SJ (TILL 1992)



SWING REDUCTION UNIT

Capacity: 44,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Check every 1 months/ 250 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Check every 1 months/ 250 hours*

TRACK PINS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

TRACK ROLLERS & IDLERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.