

| ENGINE 3412E<br>Capacity: 83 liter |                          |                          |
|------------------------------------|--------------------------|--------------------------|
| USE                                |                          | CLIMATE                  |
| Normal                             |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP 10W-40               | Agridiesel CRD+ 15W-40   | Dieselfleet CD+ 15W-40   |

Check every 10 hours, change every 1 months/ 250 hours

Check every 10 hours, change every 24 months/ 4000 hours

| HYDRAULIC SYSTEM Capacity: 891 liter (Hydraulic tank), Capacity: 1686 liter (System) |                          |                          |  |  |
|--|--------------------------|--------------------------|--|--|
| USE  |                          | CLIMATE                  |  |  |
| Normal   |                          | Mediterranean            |  |  |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 |                          |  |  |
| Multifleet SCD 30  | Gear Oil Alcat 30        |                          |  |  |
| Check every 10 hours, change every   | 24 months/ 4000 hours    |                          |  |  |
| USE  |                          | CLIMATE                  |  |  |
| Normal   |                          | Moderate                 |  |  |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |  |
| Agridiesel CRD+ 15W-40   | Agrifluid HT-Plus        | Kroontrak MTH 10W-30     |  |  |
| Check every 10 hours, change every 24 months/ 4000 hours                             |                          |                          |  |  |
| USE  |                          | CLIMATE                  |  |  |
| Biodegradable oil  |                          | Moderate                 |  |  |
| PRODUCT RECOMMENDATION 1   |                          |                          |  |  |
| Perlus Biosynth 46   |                          |                          |  |  |

#### **GREASE POINTS/NIPPLES**

We are unable to give a standard recommendation for this component. Please contact our service department.

| COOLING SYSTEM Capacity: 113 liter                        |          |  |
|---|----------|--|
| USE   | CLIMATE  |  |
| Flexible (max)  | Moderate |  |
| PRODUCT RECOMMENDATION 1                                  |          |  |
| Coolant SP 17   |          |  |
| Check every 10 hours, change every 72 months/ 12000 hours |          |  |



| SWING GEAR<br>Capacity: 274 liter                                  |                            |          |
|--|----------------------------|----------|
| USE  |                            | CLIMATE  |
| Normal   |                            | Moderate |
| PRODUCT RECOMMENDATION 1   |                            |          |
| MoS2 Grease EP 2   |                            |          |
| Check every 12 months/ 2000 hours                                  |                            |          |
|  |                            |          |
| SWING REDUCTION UNIT Capacity: 14 liter (each), Capacity: 38 liter | (Total system volume)      |          |
| USE  |                            | CLIMATE  |
| Normal   |                            | Moderate |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2   |          |
| Gear Oil Alcat 30  | Gear Oil Alcat 50          |          |
| Check every 1 months/ 250 hours, change                            | every 6 months/ 1000 hours |          |
| USE  |                            | CLIMATE  |
| Normal   |                            | Arctic   |
| PRODUCT RECOMMENDATION 1   |                            |          |
| Gear Oil Alcat 10W   |                            |          |
| Check every 1 months/ 250 hours, change                            | every 6 months/ 1000 hours |          |
| USE  |                            | CLIMATE  |
| Initial service  |                            | Moderate |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2   |          |
| Gear Oil Alcat 30  | Gear Oil Alcat 50          |          |
| Change every 250 hours/ 6 months                                   |                            |          |
| USE  |                            | CLIMATE  |
| Initial service  |                            | Arctic   |
| PRODUCT RECOMMENDATION 1   |                            |          |
| Gear Oil Alcat 10W   |                            |          |
| Change every 250 hours/ 6 months                                   |                            |          |



| Normal Normal Multifleet SCD 40  JSE CLIMATE Normal  Modera  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  TRACK ROLLERS JSE CLIMATE Normal Multifleet SCD 30  Multifleet SCD 30  TRACK ROLLERS JSE CLIMATE Normal Multifleet SCD 40                     |       |
|---|-------|
| Multifleet SCD 40  JSE  CLIMATE Normal  Modera  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  TRACK ROLLERS  JSE  CLIMATE Modera  CLIMATE Modera  Multifleet SCD 30  CLIMATE Modera  Multifleet SCD 30  CLIMATE Modera  Mediter  RODUCT RECOMMENDATION 1 |       |
| Multifleet SCD 40  USE VORMAL  PRODUCT RECOMMENDATION 1  Multifleet SCD 30   TRACK ROLLERS USE VORMAL  PRODUCT RECOMMENDATION 1  Mediter PRODUCT RECOMMENDATION 1   | e     |
| CLIMATE Moderal Moderal Moderal Multifleet SCD 30  TRACK ROLLERS USE CLIMATE CLIMATE Mediter CRODUCT RECOMMENDATION 1  TRACK ROLLERS USE CLIMATE Mediter CRODUCT RECOMMENDATION 1   | е     |
| Normal Moderal PRODUCT RECOMMENDATION 1 Multifleet SCD 30  FRACK ROLLERS USE CLIMATE Normal Mediter PRODUCT RECOMMENDATION 1  | e     |
| TRACK ROLLERS USE CLIMATE Normal Mediter PRODUCT RECOMMENDATION 1   | e     |
| Multifleet SCD 30  FRACK ROLLERS  USE  Vormal  PRODUCT RECOMMENDATION 1   |       |
| TRACK ROLLERS  USE  Vormal  PRODUCT RECOMMENDATION 1  |       |
| Normal Mediter Product RECOMMENDATION 1   |       |
| Normal Mediter Product RECOMMENDATION 1   |       |
| Normal Mediter Product RECOMMENDATION 1   |       |
| PRODUCT RECOMMENDATION 1  |       |
|   | anean |
| Multifleet SCD 40   |       |
|   |       |
| JSE CLIMATE   |       |
| Normal Modera   |       |
| PRODUCT RECOMMENDATION 1  | е     |
| Multifleet SCD 30   | e     |
|   | e     |



| TRAVEL REDUCTION UNIT Capacity: 22 liter (each)                    |                          |          |  |  |
|--|--------------------------|----------|--|--|
| USE  |                          | CLIMATE  |  |  |
| Normal   |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 |          |  |  |
| Gear Oil Alcat 30  | Gear Oil Alcat 50        |          |  |  |
| Check every 1 months/ 250 hours, change every 6 months/ 1000 hours |                          |          |  |  |
| USE  |                          | CLIMATE  |  |  |
| Normal   |                          | Arctic   |  |  |
| PRODUCT RECOMMENDATION 1   |                          |          |  |  |
| Gear Oil Alcat 10W   |                          |          |  |  |
| Check every 1 months/ 250 hours, change every 6 months/ 1000 hours |                          |          |  |  |
| USE  |                          | CLIMATE  |  |  |
| Initial service  |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 |          |  |  |
| Gear Oil Alcat 30  | Gear Oil Alcat 50        |          |  |  |
| Change every 250 hours/ 6 months                                   |                          |          |  |  |
| USE  |                          | CLIMATE  |  |  |
| Initial service  |                          | Arctic   |  |  |
| PRODUCT RECOMMENDATION 1   |                          |          |  |  |
| Gear Oil Alcat 10W   |                          |          |  |  |
| Change every 250 hours/ 6 months                                   |                          |          |  |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.