

| ENGINE C9 Acert<br>Capacity: 35,5 liter |                          |                          |
|---|--------------------------|--------------------------|
| USE                                     |                          | CLIMATE                  |
| Normal                                  |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1                | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40                  | Dieselfleet CD+ 15W-40   | Multifleet SHPD 15W-40   |
| Check every 10 hours, change every 3 mo | nths/ 500 hours          |                          |
| USE                                     |                          | CLIMATE                  |
| Normal                                  |                          | Moderate                 |
|   |                          |                          |

Check every 10 hours, change every 3 months/ 500 hours

| HYDRAULIC SYSTEM<br>Capacity: 194 liter (Refill) |               |
|--|---------------|
| USE  | CLIMATE       |
| Normal   | Mediterranean |
| PRODUCT RECOMMENDATION 1                         |               |
| Gear Oil Alcat 30                                |               |

Check every 10 hours, change every 1000 hours/ 12 months

| USE                      |                          | CLIMATE                   |
|--------------------------|--------------------------|---------------------------|
| Normal                   |                          | Moderate                  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
| Kroontrak CVT 10W-40     | Agridiesel CRD+ 15W-40   | Agrifluid Synth XHP Ultra |

Check every 10 hours, change every 1000 hours/ 12 months

| USE                                |                          | CLIMATE                   |
|------------------------------------|--------------------------|---------------------------|
| Continuous hammer use              |                          | Mediterranean             |
| PRODUCT RECOMMENDATION 1           |                          |                           |
| Gear Oil Alcat 30                  |                          |                           |
| Check every 10 hours, change every | 600 hours                | ,                         |
| USE                                |                          | CLIMATE                   |
| Continuous hammer use              |                          | Moderate                  |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
| Kroontrak CVT 10W-40               | Agridiesel CRD+ 15W-40   | Agrifluid Synth XHP Ultra |

Check every 10 hours, change every 600 hours



| USE                                    |         | CLIMATE       |
|--|---------|---------------|
| Partial hammer use (50%)               |         | Mediterranean |
| PRODUCT RECOMMENDATION 1               |         |               |
| Gear Oil Alcat 30                      |         |               |
| Check every 10 hours, change every 100 | 0 hours |               |
| USE                                    |         | CLIMATE       |

| Kroontrak CVT 10W-40     | Agridiesel CRD+ 15W-40   | Agrifluid Synth XHP Ultra |
|--------------------------|--------------------------|---------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
| Partial hammer use (50%) |                          | Moderate                  |
| 00E                      |                          |                           |

Check every 10 hours, change every 1000 hours

| COOLING SYSTEM<br>Capacity: 36,5 liter  |                    |          |
|---|--------------------|----------|
| USE                                     |                    | CLIMATE  |
| Normal                                  |                    | Moderate |
| PRODUCT RECOMMENDATION 1                |                    |          |
| Coolant SP 17                           |                    |          |
| Check every 10 hours, change every 72 m | onths/ 12000 hours |          |

| SWING GEAR<br>Capacity: 29 liter   |                          |                          |
|------------------------------------|--------------------------|--------------------------|
| USE                                |                          | CLIMATE                  |
| Normal                             |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease                      | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |
| Change every 1000 hours/ 12 months |                          |                          |



| SWING REDUCTION UNIT<br>Capacity: 19 liter |                            |          |
|--|----------------------------|----------|
| USE  |                            | CLIMATE  |
| Normal                                     |                            | Moderate |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2   |          |
| Gear Oil Alcat 30                          | Gear Oil Alcat 50          |          |
| Check every 1 months/ 250 hours, change    | every 6 months/ 1000 hours |          |
| USE  |                            | CLIMATE  |
| Normal                                     |                            | Arctic   |
| PRODUCT RECOMMENDATION 1                   |                            |          |
| Gear Oil Alcat 10W                         |                            |          |
| Check every 1 months/ 250 hours, change    | every 6 months/ 1000 hours |          |
| USE  |                            | CLIMATE  |
| Initial service                            |                            | Moderate |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2   |          |
| Gear Oil Alcat 30                          | Gear Oil Alcat 50          |          |
| Change every 250 hours                     |                            |          |
| USE  |                            | CLIMATE  |
| Initial service                            |                            | Arctic   |
| PRODUCT RECOMMENDATION 1                   |                            |          |
| Gear Oil Alcat 10W                         |                            |          |
| Change every 250 hours                     |                            |          |
|  |                            |          |



|                             | CLIMATE   |
|-----------------------------|---|
|                             | Moderate  |
| PRODUCT RECOMMENDATION 2    |   |
| Gear Oil Alcat 50           |   |
| every 12 months/ 2000 hours |   |
|                             | CLIMATE   |
|                             | Arctic  |
|                             |   |
|                             |   |
| every 12 months/ 2000 hours |   |
|                             | CLIMATE   |
|                             | Moderate  |
| PRODUCT RECOMMENDATION 2    |   |
| Gear Oil Alcat 50           |   |
|                             |   |
|                             | CLIMATE   |
|                             | Arctic  |
|                             |   |
|                             |   |
|                             |   |
|                             | Gear Oil Alcat 50<br>e every 12 months/ 2000 hours<br>e every 12 months/ 2000 hours<br>PRODUCT RECOMMENDATION 2 |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.