

# CATERPILLAR VIBRATORY COMPACTORS

## CB/CC/CD/CP/CS CB-544 8FM



**ENGINE** Caterpillar  
Capacity: 9 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| <b>Multifleet SCD 40</b> | <b>Multifleet SCD 30</b> |

*Check every 10 hours, change every 250 hours/ 3 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
|-------------------------------|-----------------------------|-----------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |

*Check every 10 hours, change every 250 hours/ 3 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

| PRODUCT RECOMMENDATION 1  |  |
|---------------------------|--|
| <b>Multifleet SCD 10W</b> |  |

*Check every 10 hours, change every 250 hours/ 3 months*

**HYDRAULIC SYSTEM**  
Capacity: 54,9 liter (Hydraulic tank)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|--------------------------|
| <b>Multifleet SCD 30</b> | <b>Gear Oil Alcat 30</b> |

*Check every 10 hours, change every 1000 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Check every 10 hours, change every 1000 hours/ 12 months*

### GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>MoS2 Grease EP 2</b>  |  |

# CATERPILLAR VIBRATORY COMPACTORS

## CB/CC/CD/CP/CS CB-544 8FM



### COOLING SYSTEM

Capacity: 21,5 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 17</b>     |  |          |

*Check every 10 hours, change every 2000 hours/ 24 months*

### VIBRATORY BEARING RESERVOIR OIL

Capacity: 1,4 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Preferred                |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Abacot MEP HD 220</b> |  |          |

*Check every 50 hours, change every 1000 hours/ 12 months*

| USE                         |                          | CLIMATE  |
|-----------------------------|--------------------------|----------|
| Alternative (acceptable)    |                          | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2 |          |
| <b>Abacot MEP Synth 220</b> | <b>Abacot MEP 220</b>    |          |

*Check every 50 hours, change every 1000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*