

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB-564D D4M (2005 AND AFTER)



ENGINE Caterpillar 3054C
Capacity: 9 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	

Check every 10 hours, change every 500 hours/ 6 months

HYDRAULIC SYSTEM
Capacity: 60 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 10 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB-564D D4M (2005 AND AFTER)

**COOLING SYSTEM**

Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 36 months/ 6000 hours

ECENTRIC WEIGHT HOUSING

Capacity: 11,8 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	

Check every 3 months/ 250 hours, change every 36 months/ 3000 hours

ECENTRIC WEIGHT HOUSING Versa Vibe

Capacity: 9 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	

Check every 3 months/ 250 hours, change every 36 months/ 3000 hours

PLANETARY DRUM DRIVE

Capacity: 2,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	

Check every 3 months/ 250 hours, change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	

Change every 250 hours/ 6 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.