

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CP-563C 4LN00001 -> 00806 (1995-2000)



ENGINE 3116T
Capacity: 20 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours/ 3 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Check every 10 hours, change every 250 hours/ 3 months

TRANSAXLE
Capacity: 27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

HYDRAULIC SYSTEM
Capacity: 110 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	

Check every 10 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 1000 hours/ 12 months

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CP-563C 4LN00001 -> 00806 (1995-2000)



GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

USE	CLIMATE
Light Duty	Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

PRODUCT RECOMMENDATION 2

Labora Grease

COOLING SYSTEM

Capacity: 33,1 liter

USE	CLIMATE
Preferred, extended	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Check every 10 hours, change every 72 months/ 6000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF*Check every 10 hours, change every 24 months/ 3000 hours*

ECCENTRIC WEIGHT HOUSING

Capacity: 55 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube HS GL-5 80W-140*Check every 3 months/ 250 hours, change every 12 months/ 1000 hours*

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CP-563C 4LN00001 -> 00806 (1995-2000)

**FINAL DRIVE - DRUM**

Capacity: 3,2 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP Synth 220		

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

VIBRATORY SUPPORT

Capacity: 0,85 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube HS GL-5 80W-140

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.