DOOSAN (DAEWOO) TRACKED EXCAVATORS SOLAR, S-SERIES SOLAR 15 PLUS MITSUBISHI L3E (2002-2008)

ENGINE Mitsubishi L3E
Capacity: 3,6 liter

USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**	
Kroontrak CVT 10W-40	**Agrisynth MSP 10W-40**	**Agridiesel MSP 15W-40**	

Change every 250 hours/ 6 months

USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**	
Kroontrak CVT 10W-40	**Agrisynth MSP 10W-40**	**Agridiesel MSP 15W-40**	

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 26 liter (Tank)

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**
Perlus H 46	**Perlus H 32**

GREASE POINTS/NIPPLES

USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**	
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**	

COOLING SYSTEM

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**
Coolant -38 Organic NF	**Coolant -26**

DOOSAN (DAEWOO) TRACKED EXCAVATORS SOLAR, S-SERIES SOLAR 15 PLUS MITSUBISHI L3E (2002-2008)

TRAVEL REDUCTION UNIT
Capacity: 0,33 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.