JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 536-70 USA (108 KW) STAGE IIIB/T4I (2014 AND AFTER)



ENGINE JCB Ecomax T4i Capacity: 15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Armado Synth MSP 5W-40	
Check every 10 hours, change every 500 hours/ 6 months	

DIFFERENTIAL FRONT Capacity: 17,7 liter	
use Normal	CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Agrifluid HT	

Check every 50 hours, change every 6 months/ 500 hours

DIFFERENTIAL REAR Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
	4 /=001	

Check every 50 hours, change every 6 months/ 500 hours

HUB REDUCTIONS FRONT Capacity: 1,9 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 6 months/ 500 hours	

HUB REDUCTIONS REAR Capacity: 2 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 6 months/ 500 hours	

HYDRAULIC SYSTEM

Capacity: 115 liter (Hydraulic tank)

JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 536-70 USA (108 KW) STAGE IIIB/T4I (2014 AND AFTER)



TRANSMISSION POWERSHIFT PS760 Capacity: 21 liter (Change capacity), Capa	city: 23 liter (Dry fill)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 1000	hours/ 12 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every 1000	hours/ 12 months	

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
Check every 50 hours, change ever	y 2000 hours/ 24 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	
Check every 50 hours, change ever	y 2000 hours/24 months	

HYDRAULIC BRAKE SYSTEM		
CLIMATE		
Moderate		

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Preferred		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
HT Q9 High Grade Grease	Labora Grease		

JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 536-70 USA (108 KW) STAGE IIIB/T4I (2014 AND AFTER)



COOLING SYSTEM Capacity: 28 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
011	20001 /24 //	

Check every 10 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.