

JCB TELESCOPIC HANDLERS TM320WM

ECOMAX T4F (SCR)



ENGINE JCB Ecomax T4f (SCR)
Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Armado Synth LSP Ultra 5W-30	Dieselfleet MSP 10W-30

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT
Capacity: 17,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 500 hours/ 12 months

DIFFERENTIAL REAR
Capacity: 17,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 500 hours/ 12 months

TRANSFERBOX

JCB TELESCOPIC HANDLERS TM320WM

ECOMAX T4F (SCR)

**TRANSMISSION POWERSHIFT PS760**

Capacity: 19 liter (Dry fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 10 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 10 hours, change every 1000 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 97 liter (Hydraulic tank), Capacity: 135 liter (System)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

PRODUCT RECOMMENDATION 2

Perlus H 46*Check every 10 hours, change every 1000 hours/ 12 months*

USE

JCB TELESCOPIC HANDLERS TM320WM ECOMAX T4F (SCR)



Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.