JCB TRACKED EXCAVATORS 803 PLUS (1995-2000)



ENGINE Perkins 103-15		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Change every 100 hours	-	
HYDRAULIC SYSTEM		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Change every 1000 hours		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Change every 1000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 1000 hours		

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Mediterranean
USE		CLIMATE
GREASE POINTS/NIPPLES		

JCB TRACKED EXCAVATORS 803 PLUS (1995-2000)



SLEW DRIVE GEARBOX	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Perlus H 68	
Change every 1000 hours	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 1000 hours	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 1000 hours	

SLEW RING BEARINGS		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SLEW RING GEAR TEETH	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Compound OGL	

TRACK DRIVE GEARBOXES	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Change even 1000 hours	

Change every 1000 hours

JCB TRACKED EXCAVATORS 803 PLUS (1995-2000)



TRACK IDLER WHEELS		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.