## JCB TRACKED EXCAVATORS 8080 ZTS ISUZU 4JG1 STAGE II/T2 (2003-2009)



| ENGINE Isuzu 4JG1<br>Capacity: 9,6 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE                                      |                          | CLIMATE                  |
| Normal                                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40                   | Synfleet SHPD 10W-40     | Dieselfleet CD+ 15W-40   |

| HYDRAULIC SYSTEM Capacity: 105 liter (Hydraulic system including tank), Capacity: 56,5 liter (Hydraulic tank) |  |  |  |
|---|--|--|--|
| CLIMATE   |  |  |  |
| Moderate  |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |

| GREASE POINTS/NIPPLES |                          |                       |
|-----------------------|--------------------------|-----------------------|
| use<br>Normal         |                          | climate<br>Moderate   |
|                       |                          |                       |
| Labora Grease         | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| COOLING SYSTEM Capacity: 14 liter |                          |                    |  |
|-----------------------------------|--------------------------|--------------------|--|
| use<br>Normal                     |                          | сымате<br>Moderate |  |
|                                   |                          |                    |  |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 |                    |  |
| Coolant -38 Organic NF            | Coolant -26              |                    |  |

| TRACK DRIVE GEARBOXES Capacity: 1,3 liter (each) |                             |          |
|--|-----------------------------|----------|
| USE  |                             | CLIMATE  |
| Normal   |                             | Moderate |
| PRODUCT RECOMMENDATION 1                         | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                             | Unigear HS GL-3/GL-5 80W-90 |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.