

# JCB TRACKED EXCAVATORS JS-130 LC STAGE IIIB/T4I (2012-2016)



**ENGINE** JCB Ecomax (SH)  
Capacity: 20,4 liter

**USE**  
Normal

**CLIMATE**  
Mediterranean

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 3 months/ 500 hours*

**USE**  
Severe

**CLIMATE**  
Mediterranean

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 250 hours/ 3 months*

## HYDRAULIC SYSTEM

Capacity: 124 liter, Capacity: 73 liter (Hydraulic tank)

**USE**  
Normal

**CLIMATE**  
Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus H 68**

PRODUCT RECOMMENDATION 3

**Perlus AF 46**

*Check every 800 hours, change every 24 months/ 4000 hours*

**USE**  
Normal

**CLIMATE**  
Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 32**

PRODUCT RECOMMENDATION 2

**Perlus AF 32**

*Check every 800 hours, change every 24 months/ 4000 hours*

**USE**  
Biodegradable oil

**CLIMATE**  
Moderate

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

*Check every 10 hours, change every 2000 hours/ 12 months*

**USE**  
Breaker, Crusher or Pulverizer = 10-25% of total use

**CLIMATE**  
Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus H 68**

PRODUCT RECOMMENDATION 3

**Perlus AF 46**

*Check every 600 hours, change every 24 months/ 3000 hours*

# JCB TRACKED EXCAVATORS JS-130 LC STAGE IIIB/T4I (2012-2016)



USE		CLIMATE
Breaker, Crusher or Pulverizer = 10-25% of total use		Moderate
PRODUCT RECOMMENDATION 1 <b>Perlus H 32</b>	PRODUCT RECOMMENDATION 2 <b>Perlus AF 32</b>	
<i>Check every 600 hours, change every 24 months/ 3000 hours</i>		
USE		CLIMATE
Breaker, Crusher or Pulverizer = 25-50% of total use		Mediterranean
PRODUCT RECOMMENDATION 1 <b>Perlus H 46</b>	PRODUCT RECOMMENDATION 2 <b>Perlus H 68</b>	PRODUCT RECOMMENDATION 3 <b>Perlus AF 46</b>
<i>Check every 300 hours, change every 24 months/ 1500 hours</i>		
USE		CLIMATE
Breaker, Crusher or Pulverizer = 25-50% of total use		Moderate
PRODUCT RECOMMENDATION 1 <b>Perlus H 32</b>	PRODUCT RECOMMENDATION 2 <b>Perlus AF 32</b>	
<i>Check every 300 hours, change every 24 months/ 1500 hours</i>		
USE		CLIMATE
Breaker, Crusher or Pulverizer = 50-75% of total use		Mediterranean
PRODUCT RECOMMENDATION 1 <b>Perlus H 46</b>	PRODUCT RECOMMENDATION 2 <b>Perlus H 68</b>	PRODUCT RECOMMENDATION 3 <b>Perlus AF 46</b>
<i>Check every 200 hours, change every 1000 hours/ 24 months</i>		
USE		CLIMATE
Breaker, Crusher or Pulverizer = 50-75% of total use		Moderate
PRODUCT RECOMMENDATION 1 <b>Perlus H 32</b>	PRODUCT RECOMMENDATION 2 <b>Perlus AF 32</b>	
<i>Check every 200 hours, change every 1000 hours/ 24 months</i>		
USE		CLIMATE
Breaker, Crusher or Pulverizer > 75% of total use		Mediterranean
PRODUCT RECOMMENDATION 1 <b>Perlus H 46</b>	PRODUCT RECOMMENDATION 2 <b>Perlus H 68</b>	PRODUCT RECOMMENDATION 3 <b>Perlus AF 46</b>
<i>Check every 200 hours, change every 600 hours</i>		
USE		CLIMATE
Breaker, Crusher or Pulverizer > 75% of total use		Moderate
PRODUCT RECOMMENDATION 1 <b>Perlus H 32</b>	PRODUCT RECOMMENDATION 2 <b>Perlus AF 32</b>	
<i>Check every 200 hours, change every 600 hours</i>		

# JCB TRACKED EXCAVATORS JS-130 LC STAGE IIIB/T4I (2012-2016)



## GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>HT Q9 High Grade Grease</b>		
<i>Check every 10 hours</i>		

## GREASE POINTS/NIPPLES RECOIL SPRING CYLINDER

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>HT Q9 High Grade Grease</b>		

## COOLING SYSTEM

Capacity: 19,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>
<i>Check every 10 hours, change every 2000 hours/ 12 months</i>		

## SWING REDUCTION UNIT

Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	
<i>Check every 1 months/ 250 hours, change every 3 months/ 500 hours</i>		

## SWING RING BEARINGS

Capacity: 0,06 kg

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>HT Q9 High Grade Grease</b>		
<i>Change every 50 hours</i>		

# JCB TRACKED EXCAVATORS JS-130 LC STAGE IIIB/T4I (2012-2016)



## SWING RING GEAR TEETH

Capacity: 11 kg

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**HT Q9 High Grade Grease***Change every 500 hours*

## TRACK IDLERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 50 hours*

## TRACK ROLLERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 10 hours*

## TRAVEL REDUCTION UNIT

Capacity: 3,5 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 1 months/ 250 hours, change every 3 months/ 500 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.