PRODUCT RECOMMENDATION

JCB TRACKED EXCAVATORS MICRO PLUS STAGE IIIA/T3 (M1007129 ->) (2004-2014)

ENGINE Perkins 403D-11
Capacity: 4,9 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	

Check every 10 hours, change every 3 months/ 500 hours

HYDRAULIC SYSTEM
Capacity: 16 liter (Hydraulic tank), Capacity: 21 liter (System)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	**Perlus AF 46**	

Check every 10 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES OTHERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Check every 10 hours

COOLING SYSTEM
Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 10 hours, change every 2000 hours/ 24 months

SWING RING BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Check every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

JCB TRACKED EXCAVATORS MICRO PLUS STAGE IIIA/T3 (M1007129 ->) (2004-2014)

SWING RING GEAR TEETH

We are unable to give a standard recommendation for this component. Please contact our service department.

TRAVEL REDUCTION UNIT

Capacity: 0,3 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 1 months/ 250 hours, change every 3 months/ 500 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367