## JCB WHEELED LOADERS 411 STAGE II/T2 (1241500->) (2001-2008)



<b>ENGINE</b> Perkins 1104-44TA Capacity: 10,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT JCB PD70 Capacity: 24 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 6 months/ 500 hours, change	every 12 months/ 1000 hours	
USE		CLIMATE
Initial convice		Madarata

SOF .	VEIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
01	

Change every 100 hours

DIFFERENTIAL REAR JCB PD70 Capacity: 24 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
01 1001	

Change every 100 hours

## **JCB WHEELED LOADERS 411 STAGE II/T2** (1241500->)(2001-2008)



TRANSMISSION ZF 4WG115 4/3 Capacity: 18 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

Check every 50 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM Capacity: 110 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Check even 10 hours, change even 1000 hours (12 months		

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		
Charle avery 10 hours, shares avery 1000 hours/12 months		

Check every 10 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

COOLING SYSTEM Capacity: 26 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 6 months/ 500 hours, change every 24 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.