JCB WHEELED LOADERS 446B HT CUMMINS 6CT8.3 (1998-2000)



Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
	Mediterranean
	CLIMATE
	PRODUCT RECOMMENDATION 2

Change every 250 hours

DIFFERENTIAL FRONT	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 500 hours	

DIFFERENTIAL REAR	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 500 hours	

HUB REDUCTIONS FRONT	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 500 hours	·

HUB REDUCTIONS REAR			
USE	CLIMATE		
Normal	Mediterranean		
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Change every 500 hours			

JCB WHEELED LOADERS 446B HT CUMMINS 6CT8.3 (1998-2000)



TRANSMISSION ZF	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 1000 hours	

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 2000 hours	·

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.