PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U KX057-4 KUBOTA V2607-DI-E3-BH (2009 AND AFTER)

ENGINE Kubota V2607-DI-E3B
Capacity: 9 liter

USE		CLIMATE
Normal, fuel sulfur level < 0,1 %		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SCD 30**

Change every 500 hours

USE		CLIMATE
Normal, fuel sulfur level < 0,1 %		Cold
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Multifleet SCD 20W-20	**Multifleet SCD 10W**	

Change every 500 hours

HYDRAULIC SYSTEM
Capacity: 45 liter (Hydraulic tank), Capacity: 79 liter (Total)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Perlus H 46	**Perlus H 68**	**Perlus AF 46**

Change every 1000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Perlus H 32	**Perlus AF 32**	

Change every 1000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U KX057-4 KUBOTA V2607-DI-E3-BH (2009 AND AFTER)

COOLING SYSTEM
Capacity: 8,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Change every 24 months

TRAVEL REDUCTION UNIT
Capacity: 0,9 liter (each)

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	**Gearlube GL-5 85W-140**	**Unigear LS GL-3/GL-5 85W-140**

Change every 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 500 hours

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	**Gearlube GL-5 85W-140**	**Unigear LS GL-3/GL-5 85W-140**

Change every 50 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367