

		A
use Normal		CLIMATE
		Tropical
PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
Check every 10 hours, change every	200 hours	
JSE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40	PRODUCT RECOMMENDATION 3 Multifleet SCD 20W-20
Check every 10 hours, change every	200 hours	,
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30		
Check every 10 hours, change every	200 hours	
use Normal		climate Arctic
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
Check every 10 hours, change every	200 hours	
use Normal, low sulphur fuel		сымате Tropical
PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
Check every 10 hours, change every	200 hours	,
use Normal, low sulphur fuel		climate Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Check every 10 hours, change every	200 hours	
use Normal, low sulphur fuel		сымате Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40



USE		CLIMATE
Normal, low sulphur fuel		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 10 hours, change every 200 l	hours	
USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 50 hours		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 20W-20
Change every 50 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Change every 50 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 50 hours		
DIFFERENTIAL FRONT (4x4) Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 400 hours		



KNUCKLE CASE FRONT (4x4) Capacity: 0,25 liter (each)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 400 hours	

TRANSMISSION CONTINUOUSLY VARIABLE HYDROSTATIC VHT Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 400 hours		

HYDRAULIC SYSTEM Capacity: 18 liter (Hydraulic tank)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 200 hours	

HYDRAULIC BRAKE SYSTEM Capacity: 0,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 24 months	'

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2



COOLING SYSTEM Capacity: 7,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 24 months	·	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.