## KUBOTA WHEELED LOADERS R/RT R420S KUBOTA D1503-M-T-E2 (2004-2013)



<b>ENGINE</b> Kubota D1503-M-T-E2 Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Change every 250 hours/ 6 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
	1	

Change every 50 hours

DIFFERENTIAL FRONT Capacity: 3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Charles aver EOO hours aborred ou		

Check every 500 hours, change every 1000 hours

Agrifluid HT-Plus	Agrifluid HT		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Initial service		Moderate	
USE		CLIMATE	

Change every 500 hours

DIFFERENTIAL REAR Capacity: 3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 500 hours, change every 1000 hours

use Initial service		CLIMATE	
		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Charge aver 500 hours			

Change every 500 hours

## KUBOTA WHEELED LOADERS R/RT R420S KUBOTA D1503-M-T-E2 (2004-2013)



HYDRAULIC SYSTEM Capacity: 42 liter (Hydraulic tank), Capacity: 60 liter (Total system volume)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	
Change every 1000 hours			
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	
Character average E00 hours	•	•	

Change every 500 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

## KUBOTA WHEELED LOADERS R/RT R420S KUBOTA D1503-M-T-E2 (2004-2013)



COOLING SYSTEM Capacity: 6,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.