

MANITOU MANISCOPIC MLT MLT 634-120

MERCEDES OM904LA (2012 AND AFTER)



ENGINE Mercedes-Benz OM904LA
Capacity: 16 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|------------------------------|-------------------------------|
| Agrisynth MSP 10W-40 | Agridiesel MSP 15W-40 | Dieselfleet MSP 15W-40 |

Check every 8 hours, change every 6 months/ 500 hours

ANGLE GEARBOX
Capacity: 2,2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 1000 hours/ 12 months

DIFFERENTIAL FRONT
Capacity: 8,1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Agrifluid HT | | |

Change every 6 months/ 500 hours

DIFFERENTIAL REAR
Capacity: 8,1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Agrifluid HT | | |

Change every 6 months/ 500 hours

HUB REDUCTIONS FRONT
Capacity: 0,8 liter (each)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 6 months/ 500 hours

MANITOU MANISCOPIC MLT MLT 634-120

MERCEDES OM904LA (2012 AND AFTER)



HUB REDUCTIONS REAR

Capacity: 0,8 liter (each)

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 6 months/ 500 hours

TRANSMISSION HYDROSTATIC

Capacity: 16,6 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Almirol | | |

Change every 1000 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 135 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 46 | | |

Change every 1000 hours/ 12 months

COOLING SYSTEM

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.