MANITOU TELESCOPIC HANDLERS MHT MHT 10210- L-E3 MERCEDES BENZ OM 904



LA

| ENGINE Mercedes-Benz OM904LA Capacity: 15,8 liter | | | |
|--|----------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Mediterranean | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Dieselfleet MSP 15W-40 | |
| Check every 10 hours, change every 500 hours/ 12 months | | | |
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Agrisynth LSP Ultra FE 5W-30 | Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40 | |

Check every 10 hours, change every 500 hours/ 12 months

| DIFFERENTIAL FRONT Capacity: 35 liter | | | |
|---|--|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| Agrifluid HT | | | |
| Check every 250 hours, change every 1000 hours/ 12 months | | | |
| USE | | CLIMATE | |
| Initial service | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| Agrifluid HT | | | |
| Change every 50 hours | | | |

| DIFFERENTIAL REAR Capacity: 35 liter | | | |
|---|---------------------|--|--|
| use Normal | climate Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | |
| Agrifluid HT | | | |
| Check every 250 hours, change every 1000 hours/ 12 months | | | |
| USE | CLIMATE | | |
| Initial service | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | |
| Agrifluid HT | | | |
| Change every 50 hours | | | |

MANITOU TELESCOPIC HANDLERS MHT MHT 10210- L-E3 MERCEDES BENZ OM 904



LA

| HUB REDUCTIONS FRONT Capacity: 6 liter (each hub) | | |
|---|---------------------|------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 250 hours, change every 500 | hours/ 12 months | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Change every 50 hours | | |
| | | |
| HUB REDUCTIONS REAR Capacity: 6 liter (each hub) | | |
| | | OLIMATE |
| use Normal | | CLIMATE Moderate |
| | | Widderate |
| PRODUCT RECOMMENDATION 1 Agrifluid HT | | |
| | | |
| Check every 250 hours, change every 500 | hours/ 12 months | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Change every 50 hours | | |
| | | |
| TRANSMISSION HYDROSTATIC 2/2 Capacity: 4,4 liter | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 250 hours, change every 100 | 00 hours/ 12 months | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Change every 50 hours | | |

MANITOU TELESCOPIC HANDLERS MHT MHT 10210- L-E3 MERCEDES BENZ OM 904



LA

| HYDRAULIC SYSTEM Capacity: 200 liter (Hydraulic tank) | | |
|---|--|---------------------|
| use Normal | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Perlus H 46 | | |
| | | |

Check every 50 hours, change every 1000 hours/ 12 months

| HYDRAULIC BRAKE SYSTEM Capacity: 0,8 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| LHM + | | |
| Check every 50 hours, change every 1000 hours/ 12 months | | |

| | CLIMATE |
|--------------------------|--------------------------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| | |

| GREASE POINTS/NIPPLES TELESCOPIC BOOM | | |
|---------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| COOLING SYSTEM Capacity: 16 liter | | |
|-----------------------------------|------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 11 | | |
| 01 | 5001 | - |

Check every 10 hours, change every 1500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.