

TERBERG RAIL ROAD LOCOMOTIVE TRACTORS RR 222 6X4 MERCEDES OM906LA STAGE 3A



ENGINE Mercedes-Benz OM906LA
Capacity: 29 liter

USE	CLIMATE
Extended, fuel sulfur level > 0,8 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Armado Synth 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 12 months/ 270 hours

USE	CLIMATE
Extended, fuel sulfur level 0 - 0,3 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Armado Synth 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 900 hours/ 12 months

USE	CLIMATE
Extended, fuel sulfur level 0,3 - 0,8 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Armado Synth 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 450 hours/ 12 months

USE	CLIMATE
Normal, fuel sulfur level 0 - 0,3 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 12 months/ 700 hours

USE	CLIMATE
Normal, fuel sulfur level 0,3 - 0,8 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 12 months/ 350 hours

USE	CLIMATE
Normal, fuel sulfur level > 0,8 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 12 months/ 210 hours

USE	CLIMATE
Alternative, fuel sulfur level 0 - 0,3 %	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 50	Multifleet SCD 40	

Check every 10 hours, change every 500 hours/ 12 months

TERBERG RAIL ROAD LOCOMOTIVE TRACTORS RR 222 6X4 MERCEDES OM906LA STAGE 3A



USE		CLIMATE
Alternative, fuel sulfur level 0 - 0,3 %		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 30	
<i>Check every 10 hours, change every 500 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0 - 0,3 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
<i>Check every 10 hours, change every 500 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0 - 0,3 %		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
<i>Check every 10 hours, change every 500 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0,3 - 0,8 %		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 50	Multifleet SCD 40	
<i>Check every 10 hours, change every 250 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0,3 - 0,8 %		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 30	
<i>Check every 10 hours, change every 250 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0,3 - 0,8 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
<i>Check every 10 hours, change every 250 hours/ 12 months</i>		
USE		CLIMATE
Alternative, fuel sulfur level 0,3 - 0,8 %		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
<i>Check every 10 hours, change every 250 hours/ 12 months</i>		

TERBERG RAIL ROAD LOCOMOTIVE TRACTORS RR 222 6X4 MERCEDES OM906LA STAGE 3A



USE		CLIMATE
Alternative, fuel sulfur level > 0,8 %		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 50	Multifleet SCD 40	

Check every 10 hours, change every 150 hours/ 12 months

USE		CLIMATE
Alternative, fuel sulfur level > 0,8 %		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 30	

Check every 10 hours, change every 150 hours/ 12 months

USE		CLIMATE
Alternative, fuel sulfur level > 0,8 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 150 hours/ 12 months

USE		CLIMATE
Alternative, fuel sulfur level > 0,8 %		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 150 hours/ 12 months

DIFFERENTIAL REAR LEADING Kessler D81DPL478 Capacity: 18 liter

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		

Change every 100 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 100 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 100 hours

TERBERG RAIL ROAD LOCOMOTIVE TRACTORS RR 222 6X4 MERCEDES OM906LA STAGE 3A



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
<i>Change every 100 hours</i>		
USE		CLIMATE
Alternative (acceptable)		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		
USE		CLIMATE
Alternative (acceptable)		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		
USE		CLIMATE
Bumpy conditions		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		

DIFFERENTIAL REAR TRAILING Kessler D81VPL478

Capacity: 18 liter

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
<i>Change every 100 hours</i>		

TERBERG RAIL ROAD LOCOMOTIVE TRACTORS RR 222 6X4 MERCEDES OM906LA STAGE 3A



USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 100 hours</i>		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Change every 100 hours</i>		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
<i>Change every 100 hours</i>		
USE		CLIMATE
Alternative (acceptable)		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		
USE		CLIMATE
Alternative (acceptable)		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		

TERBERG RAIL ROAD LOCOMOTIVE TRACTORS RR 222 6X4 MERCEDES OM906LA STAGE 3A



USE		CLIMATE
Bumpy conditions		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		

HUB REDUCTIONS REAR Kessler D81 Capacity: 1,5 liter (each)		
USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
<i>Change every 100 hours</i>		

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 100 hours</i>		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Change every 100 hours</i>		

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
<i>Change every 100 hours</i>		

USE		CLIMATE
Alternative (acceptable)		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 1 months, change every 12 months/ 1000 hours</i>		

TERBERG RAIL ROAD LOCOMOTIVE TRACTORS RR 222 6X4 MERCEDES OM906LA STAGE 3A



USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 1 months, change every 12 months/ 1000 hours

USE		CLIMATE
Alternative (acceptable)		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

Check every 1 months, change every 12 months/ 1000 hours

USE		CLIMATE
Bumpy conditions		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 1 months, change every 12 months/ 1000 hours

TRANSMISSION AUTOMATIC ZF 6WG211 6/3		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Change every 1500 hours

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Change every 100 hours

HYDRAULIC CAB TILT SYSTEM ELECTRICALLY OPERATED		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
ATF Dexron II-D	Perlus H 46	Perlus AF 46

TERBERG RAIL ROAD LOCOMOTIVE TRACTORS RR 222 6X4 MERCEDES OM906LA STAGE 3A



HYDRAULIC CAB TILT SYSTEM MANUALLY OPERATED

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

POWER STEERING TRW

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.